


## Switching Diode

### Features

- Fast Switching Speed
- Power Dissipation of 200mW
- Ultra-Small Surface Mount Package
- For General Purpose Switching Applications
- High Conductance
- RoHS Compliant




Marking: .KAC

SOT-363

### Applications

- Electronic computer
- Pulse
- Switching circuit




### Mechanical Data

- Package: SOT-363
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound
- UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 3 per J-STD-020

### Pin definition



### Equivalent circuit







Maximum Ratings & Electrical Characteristics (T <sub>A</sub> =25°C unless otherwise noted)			
Parameter	Symbol	Value	Unit
Repetitive Peak Reverse voltage	V <sub>RRM</sub>	75	V
Working Peak Reverse Voltage	V <sub>RWM</sub>	75	V
Reverse voltage	V <sub>R</sub>	75	V
Average rectified output current	I <sub>O</sub>	150	mA
Non-repetitive peak forward current	I <sub>FM</sub>	300	mA
Non-repetitive Peak Forward Surge Current @ t=8.3ms	I <sub>FSM</sub>	2	A
Power Dissipation	P <sub>D</sub>	200	mW
Thermal Resistance Junction to Ambient	R <sub>θJA</sub>	625	°C/W
Junction temperature Range	T <sub>J</sub>	-55 ~ +150	°C
Storage Temperature	T <sub>STG</sub>	-55 ~ +150	°C

Electrical Specifications (T <sub>A</sub> =25°C unless otherwise noted)					
Parameter	Symbol	Test Conditions	Limits		Unit
			Min	Max	
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>R</sub> = 2.5μA	75		V
Reverse Leakage Current	I <sub>R</sub>	V <sub>R</sub> = 20V		25	nA
		V <sub>R</sub> = 75V		2.5	uA
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = 1.0mA		0.715	V
		I <sub>F</sub> = 10mA		0.855	V
		I <sub>F</sub> = 50mA		1	V
		I <sub>F</sub> = 150mA		1.25	V
Junction Capacitance	C <sub>J</sub>	V <sub>R</sub> = 0, f = 1.0MHz		2	pF


## Ratings and Characteristics Curves

( $T_A = 25^\circ\text{C}$  unless otherwise noted)




**Soldering Parameters**

Reflow Condition		Pb -Free assembly (see as below)
Pre Heat	-Temperature Min ( $T_{s(min)}$ )	+150 °C
	-Temperature Max( $T_{s(max)}$ )	+200 °C
	-Time (Min to Max) ( $t_s$ )	60 -180 secs.
Average ramp up rate (Liquid us Temp ( $T_L$ ) to peak)		3 °C /sec. Max
$T_{s(max)}$ to $T_L$ - Ramp -up Rate		3 °C /sec. Max
Reflow	-Temperature( $T_L$ ) (Liquid us)	+217 °C
	-Temperature( $t_L$ )	60 -150 secs.
Peak Temp ( $T_p$ )		+260(+0/ -5) °C
Time within 5 °C of actual Peak Temp ( $t_p$ )		30 secs. Max
Ramp -down Rate		6 °C /sec. Max
Time 25 °C to Peak Temp ( $T_P$ )		8 min. Max
Do not exceed		+260 °C



## Package Outline Dimensions

in inches (millimeters)



SYMBOL	MILLIMETER	
	MIN	MAX
A	0.900	1.100
A1	0.000	0.100
A2	0.900	1.000
b	0.150	0.350
c	0.080	0.150
D	2.000	2.200
E	1.150	1.350
E1	2.150	2.450
e	0.650 TYP.	
e1	1.200	1.400
L	0.525 REF.	
L1	0.260	0.460
θ	0°	8°

## Revision History

Document Version	Date of release	Description of changes
Rev.A	2017.06.13	First issue

## Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.